



stilum
horse



DOUBLE-T-SLAB
500 x 500 x 23/43 mm



DOUBLE-T-SLAB

565 x 500 x 23 mm | Item-No. 2030231x1

565 x 500 x 43 mm | Item-No. 2030431x1

To renovate damaged paved surfaces, the Terrasoft Double T-Slab is often used. Here it impresses with its quick and easy installation. Another place of use are livestock pathways, such as stable lanes. Here, the Double T-Slab offers a non-slip and resilient surface, which particularly benefits the sensitive joints of large animals. For outdoor use.

Double-T-slabs 43 mm and 23 mm are made of pure rubber granules (1-3.5 mm), bound and encased with polyurethane and guarantee a permanently homogeneous surface appearance. They have a high bonding effect. With a thickness of 43 mm, the slabs can be combined with the double-T paving and the corresponding complementary bricks.

DOUBLE-T-SLAB

565 x 500 x 23 mm | Item-No. 2030231x1

565 x 500 x 43 mm | Item-No. 2030431x1

ADVANTAGES

- Minimisation of risk of injuries and breakages
- available in two thicknesses: 23 and 43 mm
- non-slip even when wet
- easy to clean
- form-fitting connection
- permeable
- sound-deadening

APPLICATION

- Pathways
- Stable aisles

NOTES

- Selective glueing of the outer slabs required
- Easy and rapid installation with the starter and half bricks (Double-T-slab 43 mm only).
- 4.5 slabs make one square metre
- We recommend the use of our bordering systems
- Please follow our detailed installation instructions to prepare the substrate.

Installation Instructions

The Terrasoft Double T Slabs are laid on solid substrates such as concrete or screed. Pay attention to a sufficient gradient. Best suited is a smooth gradient screed with subsequently applied moisture insulation as a water-bearing layer. Existing plastic sheets and bituminous membranes must first be tested for their suitability as a substrate.

Existing slabs and / or tiling must also be prepared as a flat, smooth surface with overlying moisture insulation. Unevenness must be eliminated to avoid standing pools of water. A fixed edging to maintain the position is essential.

In order to ensure the desired position in the long term, the border slabs should be glued to the substrate.

Please follow the detailed installation instructions and consider the following information. Ensure a stable edging on all sides of the area.

Dimensional tolerances may occur due to production. These will be compensated within 48 hours after installation. Please note that the final row in the installation plan will only be cut to the required size after the above-mentioned 48 hours have elapsed.

