





Double-T Solid rubber 200 x 160 x 43 mm



# **DOUBLE-T SOLID RUBBER**

200 x 160 x 43 mm | Item-No. 202143131

Wet floors imply a high risk of injury for horses. Their horseshoes let them skid easily on wet surfaces. The results are fractures, ruptures and strain traumata. Conradi+Kaiser offer ground systems and flooring, that drain water quickly and thereby minimize the risks of skidding and getting hurt. Also, if installed in solaria-bays, these springy flooring systems provide non-skid and comfortable surfaces for the horses. As a flooring for the inside of washing bays it is the double-T paving stone made from solid rubber, which is principally used. It is impermeable and skid resistant. Furthermore, it provides a durable surface, resistant to urines, and safe for horses' movements. Simple cleaning and resulting cleanliness make it an indispensible product for equestrian establishments.



### **ADVANTAGES**

- Minimisation of risk of injuries and breakages
- non-slip even when wet
- form-fitting
- impermeable
- sound-deadening

#### **APPLICATION**

- Horse walkers
- Washing-bays

### **NOTES**


- Selective glueing of the outer slabs required
- 36 bricks make one square meter
- We recommend the use of our bordering systems
- Not accessible by car/ machines
- Please follow our detailed installation instructions to prepare the substrate.


# **DOUBLE-T SOLID RUBBER**

200 x 160 x 43 mm | Item-No. 202143131


### **INSTALLATION INSTRUCTION**

It is important to ensure that the elements are placed as close together as possible. Dimensional tolerances may occur due to production. These will be compensated within 48 hours after installation. Please note that the final row in the installation plan will only be cut to the required size after the above-mentioned 48 hours have elapsed.





Laying the Terrasoft Double-T on a permeable substrate (not vehicle load-bearing).



Laying on solid surface. Bonding with gluing spots on the drainage.