

DATA SHEET MULTIPLAY TANTUM 2A

Text for invitation to tender | Item No: 51 7540 401



MATERIALS | SCOPE OF SUPPLY

Multiplay, final installation on location

Tower:	stainless steel, V2A, with steel plateau which surface is made of EPDM granules, plus walls made of HDPE panels, 2 pieces
Roof:	HDPE panels, 2 pieces
Tunnel slide:	stainless steel, V2A, 1 piece
Wobble bridge:	Herkules rope/rope/plastic, 1 piece
Climbing arc:	stainless steel, V2A, 1 piece
Climbing net:	Herkules rope/plastic, 1 piece
Balance rope:	PP/plastic, 1 piece
Rope rail:	Herkules rope/plastic, 2 piece
Helix:	stainless steel, V2A, 1 piece
Disk climbing:	stainless steel, V2A, with 11 pendulum seats made of EPDM caoutchouc and chains made of stainless steel, 1 piece
Climbing wall:	HDPE panels with climbing holds, 3 pieces
Foundation plates:	steel, coated

INSTALLATION

Foundations: 6

Installation according to our detailed mounting instructions, see www.stilum.com

TECHNICAL INFORMATION

Dimensions:

Main dimension:	11500 x 4900 mm
Height:	5450 mm
Weight:	2200 kg
Capacity:	acc. to normative requirements
Dimension largest piece:	1730 x 1250 x 5900 mm
Heaviest piece:	620 kg

Max. fall height:	3000 mm
Impact area:	82,50 m ²
Required safety slabs:	min. 91,00 m ² (□ 112,50 m ²)
Required lawn grating:	min. 104,00 m ² (□ 120,00 m ²)
Recommended surface material:	sand, wood chip, gravel, synth. impact protection

