

# DATA SHEET ROPE SWING VANNO

Text for invitation to tender | Item No: 51 2028 401

## MATERIALS | SCOPE OF SUPPLY

Rope swing, final installation on location

Tubular frame:	stainless steel, V2A, 2 pieces
Swing bar:	stainless steel, V2A, 2 pieces
Swing suspension:	Chain and Herkules-rope, 2.50 length, 14 pcs.
Swing rope:	Square cordage, 1 piece
Foundation plates:	steel, coated

## TECHNICAL INFORMATION

Dimensions:

Main dimension:	4990 x 4210 mm tolerance: $\pm 150$ mm
Height:	3290 mm tolerance: $\pm 150$ mm
Weight:	700 kg
Capacity:	acc. to normative requirements
Dimension largest piece:	2100 x 1175 x 3735 mm
Heaviest piece:	120 kg
Theoretical max. fall height:	1700 mm (60° oscillation)
Impact protection	
Impact area:	34,06 m <sup>2</sup>
Required safety slabs:	37,50 m <sup>2</sup>
Required lawn grating:	39,00 m <sup>2</sup>
Recommended surface material:	sand, wood chip, gravel, synth. impact protection

## INSTALLATION

Foundations: 4

Installation according to our detailed mounting instructions, see [www.stilum.com](http://www.stilum.com)

