

# DATA SHEET SWING VOLUCRIS 1

Text for invitation to tender | Item No: 51 2020 401

## MATERIALS | SCOPE OF SUPPLY

Swing, pre-mounted completely  
fixation of the chains necessary

Tubular frame:	stainless steel, V2A, 1 piece
Swing birdnet:	Usacord Ø 120 cm, 1 piece
Swing suspension:	chain and Herkules-rope, 1.40 m length
Foundation plates:	steel, coated

## TECHNICAL INFORMATION

Dimensions:

Main dimension:	3400 x 1200 mm tolerance: ± 150 mm
Height:	2500 mm tolerance: ± 150 mm
Weight:	195 kg
Capacity:	acc. to normative requirements
Dimension largest piece:	3470 x 1150 x 2960 mm
Heaviest piece:	151 kg

Max. fall height: 1200 mm

Impact protection

Impact area: 16,25 m<sup>2</sup>

Required safety slabs: 13,75 m<sup>2</sup>

Required lawn grating: 18,00 m<sup>2</sup>

Recommended

surface material: sand, wood chip, gravel, synth.  
impact protection

## INSTALLATION

Foundations: 2

Modified installation depth possible  
(special edition)

Installation according to our detailed mounting  
instructions, see [www.stilum.com](http://www.stilum.com)

